

SKID-STEER LOADER **S650**

Operating Weight 3777 kg
Engine Power 55.4 kW
Rated Operating Capacity 1282 kg



_				
ν_{c}	artı	orm	วท	α
1 (71 II	ULLIU	an	ᅜᅜ

Tipping load (ISO 14397-1)	2564 kg
Rated operating capacity (ISO 14397-1)	1282 kg
Pump capacity	87.1 L/min
Pump capacity (with high flow-option)	115.5 L/min
System relief at quick couplers	23.8-24.5 MPa
Max. travel speed (high range-option)	19.8 km/h
Max. travel speed (low range)	11.4 km/h

Engine

Make/Model	Kubota/V3307 (iT4)
Fuel	Diesel
Cooling	Liquid
Power at 2400 RPM (SAE J1995 Gross)	55.4 kW (74.3 HP)
Torque at 1600 RPM (SAE J1995 Gross)	264.4 Nm
Number of cylinders	4
Displacement	3331 cm ³
Fuel tank	90.51

Weights

Operating weight	3777 kg
Shipping weight without bucket	3540 kg

Controls

Vehicle steering	Direction and speed controlled by two hand levers
Loader hydraulics tilt and lift	Separate foot pedals or Selectable Joystick Control (SJC)
Front auxiliary (standard)	Electrical switch on right-hand steering lever

Tront auxiliary (standard)	Liberioal switch on right hand steering level
Drive System	
Transmission	Infinitely variable tandem hydrostatic piston pumps, driving

Standard Features

Automatically activated glow plugs Auxiliary hydraulics: variable flow/maximum flow Bob-Tach™ frame Bobcat Interlock Control System (BICS)

Operator cab1 Electrically activated proportional front auxiliary hydraulics

Engine/hydraulics system shutdown

Manual

Back-up alarm 1. Roll Over Protective Structure (ROPS) - meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I

Options

2 speed High-flow hydraulics Deluxe instrument panel

Deluxe pressurized cab with heating

Air conditioning Power Bob-Tach™

33x15.5-16.5, 12-ply, Super flotation tyres 12x16.5, 12-ply, Heavy duty tyres, offset rims

12x16.5, 12-ply, Severe duty tyres High-back adjustable suspension seat Selectable Joystick Controls (SJC)

two fully reversing hydrostatic motors

Air ride seat with 2 point seat belt Air ride seat with 3 point seat belt

12x16.5, 12-ply, Heavy duty tyres

Turbo-charger with approved spark arrestor

Beacon

Engine block heater Fire extinguisher

Lift arm support

Parking brake

Seat belt

Seat bar


Work lights, front and rear

Strobe

Deluxe operator cab with windows

Hydraulic bucket positioning(including ON/OFF switch)

Dimensions



(A)	4026.0 mm	(J)	3149.0 mm
(B)	2065.0 mm	(K)	800.0 mm
(C)	25.0°	(L)	42.0°
(D)	207.0 mm	(M)	97.0°
(E)	1150.0 mm	(N)	1880.0 mm
(F)	2754.0 mm	(0)	2106.0 mm
(G)	3474.0 mm	(P)	1507.0 mm
(H)	30.0°	(Q)	1832.0 mm
(l)	2447.0 mm		

Attachments
Angle broom
Auger
Backhoe
Blades - box, dozer, snow
snow v-blade
Breaker, hydraulic
Brush saw
Brushcat [™] rotary cutter
Bucket adapter
Buckets
Chipper
Combination bucket
Concrete pump
Digger
Drop hammer
Dumping hopper

Flail cutter Grader Grapples - farm / utility, industrial, root

Landplane Landscape rake Laser equipment Mower Packer wheel

Pallet fork Planer

Rebar bender Rock bucket Scarifier Scraper Seeder Silt fence installer Snow pusher Snowblower Sod layer Soil conditioner Spreader Stabilizer, rear Steel tracks Stump grinder Sweeper Three-point hitch adapter

Tilt-Tatch™ Tree spade Trench compactor Trencher Utility fork Utility frame Vibratory roller Water kit Wheel saw

Whisker broom

Tiller



Doosan is a global leader in construction equipment, power and water solutions, engines, and engineering Doubsil is a global electer in conscioución equipment, power and water solutions, regimes, angines propued proudly serving customers and communities for more than a century. I Bobcat and the Bobcat logo are registered trademarks of Bobcat Company in the United States and various other countries.

©2020 Bobcat Company. All rights reserved.



Doosan Bobcat Korea Co., Ltd. www.bobcat.com